

High Performance Cascadable Amplifiers

Typical and Guaranteed Specifications—50 Ω System

Model	Frequency Range MHz	Small Signal Gain dB			Gain Flatness ±dB		Noise Figure dB			Power Output At 1dB Compression dBm			Rev. Iso. dB	Intercept Point dBm	SWR In/Out		D.C.	
		Typ.	Min. 0/50C	Min. -55/85C	Max. 0/50C	Max. -55/85C	Typ.	Max. 0/50C	Max. -55/85C	Typ.	Min. 0/50C	Min. -55/85C			Typ.	3rd/2nd Typ.	Max. 0/50C	Max. -55/85C
Models listed by model number																		
AC105	1-150	15.0	14.0	13.5	0.5	0.7	2.5	3.0	3.5	15.0	14.5	14.0	27	30/42	1.9	2.0	5	35
ACH107 [^]	10-200	18.0	17.0	16.5	0.4	0.7	2.2	2.7	3.2	16.0	15.5	15.0	36	31/38	1.8/1.5	2.0/1.7	15	33
AP108	1-150	15.0	14.5	14.0	0.4	0.5	3.3	4.0	4.5	25.0	24.0	23.5	28	43/60	1.9	2.0	15	109
ARJ109 [^]	0.5-200	10.8	10.0	9.5	0.5	0.7	4.5	5.2	5.7	28.5	27.5	27.0	17	44/75	1.8	1.9	15	235
AP148	1-200	11.0	10.5	10.0	0.4	0.6	3.5	4.2	4.7	25.0	24.5	24.0	19	43/59	1.7	1.8	15	109
AC155	5-150	14.8	14.0	13.5	0.6	0.8	2.2	2.6	3.0	15.5	14.5	14.0	27	30/41	1.8/1.7	2.0/1.9	5	34
ARS169	1-150	28.3	27.0	26.0	0.5	0.8	2.3	3.2	3.8	23.0	22.0	21.5	65	40/62	1.7	2.0	15	147
ARH209 [^]	10-250	10.8	10.0	9.5	0.8	1.0	5.0	5.7	6.3	28.0	27.0	26.5	17	44/70	1.8	1.9	15	235
AC238	5-200	32.0	31.0	30.0	0.4	0.7	2.6	3.0	3.5	15.5	14.5	14.0	38	30/48.5	1.3	1.4	5	64
AC251	10-200	8.0	7.5	7.0	0.3	0.4	1.2	1.7	2.2	13.2	12.0	11.5	11	30/49	1.5	1.7	5	11
AC262	30-250	8.0	7.5	6.8	0.5	0.7	1.3	1.8	2.3	19.3	17.0	16.5	11	35/54	1.9	2.0	15	23
AC263	30-200	8.3	7.5	6.8	0.5	0.7	1.5	2.0	2.5	22.5	21.5	20.5	11	34/53	2.0	2.0	15	37
AC264	30-250	8.3	7.5	6.8	0.5	0.7	2.0	2.3	2.7	24.0	23.5	23.0	11	43/55	2.0	2.0	15	45
AC271	10-250	8.0	7.5	7.0	0.5	0.7	1.5	1.9	2.3	14.0	13.0	12.5	11	30/49	1.8	2.0	15	14.5
AC272	10-250	8.0	7.5	7.0	0.5	0.7	2.0	2.5	3.0	18.5	17.5	17.0	11	32/46	2.0	2.1	15	23
AC273 [†]	30-250	8.0	7.5	7.0	0.5	0.7	2.4	3.0	3.5	20.5	20.0	19.5	11	36/50	2.0	2.0	15	37
AC281	10-250	28.5	27.5	27.0	0.5	0.7	2.3	2.6	3.0	16.2	15.5	14.5	34	29/33	1.8/2.0	2.0/2.1	15	27
AC282	10-250	29.0	28.5	28.0	0.5	0.7	3.0	3.4	3.8	21.0	20.0	19.5	35	33/40	1.8/2.0	2.0/2.1	15	47
AC293	10-200	28.8	28.3	27.8	0.3	0.5	2.0	2.5	3.0	17.5	17.0	16.5	34	28/35	1.8	1.9	15	33
AP294	10-200	29.3	28.5	28.0	0.4	0.5	3.5	4.0	4.5	22.5	21.5	21.0	36	32/44	1.7/1.9	1.8/2.0	15	60
AC305	10-250	11.8	11.0	10.5	0.4	0.6	2.1	2.6	3.1	15.5	15.0	14.5	18	31/46	1.8/1.5	2.0/1.6	5	36
AP308	10-250	13.0	12.5	12.0	0.5	0.7	3.7	4.0	4.5	23.0	22.0	21.5	17	35/48	1.9/1.7	2.0/1.8	8	93
AC345	5-250	13.0	12.5	12.0	0.5	0.7	2.0	2.5	3.0	12.0	11.0	10.5	17	25/33	1.6/1.3	1.7/1.5	15	30
AC347	5-250	13.0	12.5	12.0	0.5	0.7	2.3	2.7	3.2	15.5	14.5	14.0	17	28/41	1.6/1.3	1.7/1.5	15	46
AP348	10-250	13.5	12.5	12.0	0.4	0.6	3.2	4.0	4.5	25.0	24.0	23.5	17	42/57	1.7	1.8	15	108
ARH356 [^]	10-300	15.5	15.0	14.5	0.3	0.4	2.5	3.0	3.5	15.0	14.5	14.0	23	32/40	1.9	2.0	5	30
AC378	5-300	14.0	13.2	13.0	0.5	0.7	5.0	6.0	6.5	19.5	18.0	17.5	18	34/49	1.7	1.8	15	65
AC379	5-300	14.0	13.2	13.0	0.5	0.7	5.0	6.0	6.5	22.5	21.5	20.5	18	39/51	1.7	1.8	15	88
AC380	10-250	25.0	24.0	23.7	0.5	0.7	1.7	2.3	2.8	9.0	7.5	7.0	30	22/31	2.0	2.0	15	17
AC381	10-250	24.0	23.0	22.7	0.5	0.7	2.7	3.3	3.8	16.0	15.0	14.5	29	29/38	2.0/1.7	2.0/1.8	15	27
AC382	10-250	24.0	23.0	22.7	0.5	0.7	3.3	4.0	4.5	21.0	20.0	19.0	29	34/43	2.0/1.7	2.0/1.8	15	47
AC383	10-250	35.0	34.0	33.0	0.7	1.0	1.7	2.5	3.0	0.5	-1.0	-2.0	47	11/19	1.7	1.9	5	14
AC386	10-250	28.0	27.0	26.5	0.7	0.8	2.6	3.3	3.8	8.0	7.5	7.0	40	20/33	1.7	1.8	5	21
AP388	10-250	14.0	13.0	12.5	0.5	0.7	5.0	5.5	6.0	23.0	22.0	21.5	20	37/45	1.9	2.0	15	65
AP389	10-250	24.5	23.0	22.5	0.7	0.8	3.3	4.3	4.8	23.0	22.0	21.5	29	36/46	1.8	1.8	15	65
AC391	10-250	24.0	23.0	22.7	0.5	0.7	3.0	3.5	4.0	19.0	18.0	17.5	29	31/40	2.0/1.7	2.0/1.8	15	37
AC437	10-400	12.7	12.0	11.5	0.5	0.7	4.7	5.3	6.0	16.5	15.5	15.0	19	32/44	1.7/2.0	1.9/2.0	15	33
AP448	10-400	10.5	10.0	9.5	0.5	0.6	4.3	4.8	5.3	24.8	24.0	23.5	17	42/53	1.7/1.5	1.8/1.6	15	110
AC453	10-400	14.8	13.5	13.0	0.5	0.7	2.8	4.0	4.5	5.5	4.5	4.0	18	17/24	1.8/2.0	1.9/2.0	5	10.5
AC457	10-400	15.3	14.5	14.0	0.7	0.9	3.0	3.5	4.0	10.5	9.0	8.5	21	25/37	1.8/2.0	1.9/2.0	5	15.5
AC487	10-400	15.5	14.5	14.0	0.7	0.9	3.6	4.0	4.5	17.0	15.5	15.0	21	32/44	1.7/2.0	1.9/2.0	15	33
AC501	5-500	16.2	15.0	14.3	0.5	0.7	2.1	3.0	3.5	-1.5	-2.0	-3.0	20	11/10	1.8	2.0	15	9
AC502	10-500	18.0	17.5	17.0	0.7	1.0	1.4	1.85	1.9	2.5	2.0	1.5	19	—	2.0	2.0	15	9
AC505	0.3-500	15.0	14.0	13.5	0.5	0.7	3.3	4.0	4.5	10.0	8.0	7.0	20	21/36	2.0	2.0	15	24
AC506	10-500	19.0	18.5	18.3	0.6	0.8	2.5	3.2	3.5	9.5	9.2	9.2	20	—	2.0	2.0	15	20
AC507	10-500	20.5	20.0	19.5	0.7	0.7	2.4	2.5	3.0	17.0	17.0	17.0	22	—	2.0	2.0	15	60

Current data sheets available on website. Shaded models indicate typical output power ≥+20 dBm. [^] Not available in surface mount package.

[†] See AC271/AC273 data sheet.

High Performance Cascadable Amplifiers

Typical and Guaranteed Specifications—50 Ω System

Model	Frequency Range MHz	Small Signal Gain dB			Gain Flatness ±dB		Noise Figure dB			Power Output At 1dB Compression dBm			Rev. Iso. dB	Intercept Point dBm 3rd/2nd Typ.	SWR In/Out		D.C.	
		Typ.	Min. 0/50C	Min. -55/85C	Max. 0/50C	Max. -55/85C	Typ.	Max. 0/50C	Max. -55/85C	Typ.	Min. 0/50C	Min. -55/85C			Typ.	Max. 0/50C	Max. -55/85C	Volts Nom.
Models listed by model number																		
AC508	5-500	16.5	15.0	14.3	0.5	0.7	2.5	3.0	3.5	-1.5	-2.0	-3.0	—	—	1.8	2.0	15	9
AC509	5-500	13.3	12.5	12.0	0.5	0.7	4.2	5.0	5.5	21.5	20.5	20.0	18	34/45	1.7	1.9	15	88
AC513	5-500	20.0	19.5	19.0	0.5	0.8	1.9	2.3	2.8	3.5	2.0	1.5	24	16/17	1.7	2.0	15	14
AC514	5-500	21.0	20.0	19.5	0.5	0.8	2.9	3.5	4.0	13.0	11.5	11.0	25	24/37	1.7	2.0	15	32
AC518	5-500	28.0	26.5	26.0	0.5	0.7	4.0	4.7	5.2	19.3	18.5	17.0	36	32/50	1.7	1.8	15	96
AC519	5-500	27.5	26.5	26.0	0.5	0.7	3.5	4.5	5.0	21.8	20.5	20.0	36	33/44	1.7	1.8	15	127
AC524	5-500	31.5	30.0	29.0	0.7	1.0	3.0	4.0	4.5	8.5	7.5	7.0	40	20/33	1.7	2.0	15	35
AC525	5-500	31.5	30.0	29.0	0.7	1.0	3.2	4.2	4.7	12.0	10.5	10.0	40	24/37	1.7	2.0	15	48
AS529	100-500	29.5	28.0	27.0	0.7	0.9	1.0	1.2	1.4	19.5	18.0	17.5	45	32/54	1.4	1.5	5	185
AC534	5-500	26.5	26.0	25.5	0.5	0.8	2.7	3.3	3.8	4.0	3.5	3.0	38	12/30	1.7	1.8	5	16
AC536	5-500	28.0	27.5	27.0	0.5	0.8	3.0	3.5	4.0	15.5	15.0	14.5	37	28/46	1.7	1.8	8	62
AC538	5-500	27.5	27.0	26.5	0.5	0.8	2.8	3.5	4.0	12.5	11.5	11.0	37	27/50	1.7	1.8	5	47
AC540	10-500	12.5	11.5	11.0	0.5	0.8	1.8	2.5	3.0	4.5	3.5	3.0	18	17/24	1.8	2.0	15	15
AC541	20-500	15.5	14.5	14.0	0.7	1.0	2.8	3.3	4.0	6.5	5.5	5.0	37	20/26	2.0/1.5	2.0/1.5	15	27
AC542	20-500	17.5	16.5	16.0	0.7	1.0	3.3	3.8	4.5	14.0	13.5	13.0	36	28/35	2.0/1.5	2.0/1.5	15	47
AC543	10-500	11.3	10.5	10.0	0.4	0.6	2.5	3.0	3.5	10.0	9.0	8.5	19	26/38	1.8	2.0	15	24
AC544	10-500	11.5	10.5	10.0	0.4	0.6	2.7	3.3	3.8	13.5	12.5	12.0	18	29/42	1.8	2.0	15	35
AC545	10-500	12.8	12.5	12.0	0.5	0.8	2.5	3.0	3.5	9.3	8.0	7.5	17	25/33	1.8	2.0	15	24
AC547	10-500	13.0	12.5	12.0	0.5	0.8	3.3	3.8	4.5	15.5	14.5	14.0	17	30/42	1.8	2.0	15	44
AC548	5-500	12.5	11.5	11.0	0.4	0.6	3.7	4.5	5.0	19.0	17.8	17.0	18	35/48	1.9/1.4	2.0/1.5	15	58
AC552	30-500	22.0	21.0	20.5	0.5	0.7	2.4	3.0	3.5	10.0	9.0	8.0	29	22/28	1.9	2.0	5	16
AC555†	0.3-500	15.0	14.0	13.5	0.5	0.7	3.8	4.5	5.0	12.5	11.0	10.5	20	25/39	2.0	2.0	15	34
AC556	5-500	28.5	27.5	27.0	0.5	0.7	3.5	4.2	4.7	14.5	14.0	13.5	38	28/38	1.8	2.0	15	65
AC557	0.3-500	15.0	14.0	13.5	0.5	0.8	4.0	5.0	5.5	14.7	13.5	13.0	20	28.5/36	1.8	2.0	15	44
AC558	5-500	11.0	10.5	10.0	0.5	0.7	5.2	6.0	6.5	19.0	18.0	17.5	16	32/50	1.8	1.9	15	65
AC559	5-500	11.0	10.5	10.0	0.5	0.7	5.7	6.5	7.0	22.0	21.0	20.5	16	35/49	1.8	1.9	15	88
AP560	10-500	13.3	12.5	12.0	0.5	0.7	4.6	5.5	6.0	24.5	23.5	23.0	17	35/36	1.7	2.0	15	130
AP561	10-500	13.5	12.5	12.0	0.5	0.7	5.0	6.5	7.0	27.0	25.0	24.5	17	41/48	1.7/1.9	1.8/2.0	15	175
AC564	5-500	36.2	35.5	35.0	0.5	0.7	2.5	3.5	4.0	11.5	10.5	10.0	46	23/35	1.7	1.8	15	48
AC566	5-500	32.5	32.0	31.5	0.5	0.7	2.8	3.5	4.0	16.0	15.0	14.5	40	30/47	1.7	1.8	15	65
AC572	5-500	15.2	14.0	13.5	0.5	0.7	3.4	4.0	5.0	12.5	11.5	11.0	19	27/35	1.7	1.8	5	29
AC573	5-500	31.5	30.0	29.0	0.7	0.9	2.4	2.8	3.3	3.0	1.0	0.5	40	15/25	1.7	1.9	15	20
AC575	5-500	21.0	20.0	19.5	0.5	0.8	2.6	3.0	3.5	10.0	8.5	8.0	25	21/31	1.7	2.0	15	24
AC576†	5-500	29.0	28.0	27.5	0.5	0.7	3.3	4.0	4.5	15.0	14.5	14.0	37	29/42	1.8	2.0	15	65
AC577	5-500	16.5	16.0	15.0	0.5	0.9	4.0	5.5	6.0	16.5	15.0	14.5	20	30/43	1.7	2.0	15	48
AC580	10-500	22.8	21.8	21.3	0.7	0.8	2.2	2.7	3.2	9.7	7.5	7.0	29	22/27	2.0	2.0	15	17
AC581	20-500	23.0	22.0	21.5	0.7	1.0	2.8	3.7	4.3	15.0	14.0	13.5	31	27/35	1.9	2.0	15	31
AC582	20-500	23.0	22.0	21.5	0.7	1.0	3.3	4.2	4.7	20.0	19.0	18.5	31	33/40	1.9	2.0	15	53
AC583	10-500	30.0	29.0	28.5	0.5	0.7	1.8	2.5	3.0	0.0	-1.0	-2.0	41	11.5/22	1.7	1.8	5	14
ARH609^	10-600	13.8	13.0	12.0	0.6	0.7	5.0	5.5	6.0	26.0	24.5	24.0	17	41/74	1.7	1.9	15	235
AC618	10-600	32.0	31.0	30.0	0.7	0.8	2.8	3.2	3.7	19.0	18.0	17.5	39	32/50	1.5	1.7	12	85
AC652	10-600	10.8	10.0	9.5	0.9	1.0	1.3	1.7	2.0	18.8	18.0	17.5	17.5	32/45	1.8	2.0	5	48.5
AC658	10-600	31.0	30.0	29.0	0.7	0.8	2.7	3.1	3.6	17.0	16.5	16.0	37	32/38	1.5	1.7	5	120
AC688	200-600	21.0	20.3	20.0	0.8	1.0	0.9	1.1	1.4	21.5	20.5	20.0	28	33/45	1.9	2.0	5	85
AC718	100-700	33.5	32.0	31.5	0.7	0.8	2.6	3.2	3.7	19.0	18.0	17.5	40	33/44	1.5	1.7	12	86
AP719	10-700	27.5	26.5	26.0	0.5	0.7	3.5	4.2	4.7	24.3	23.5	23.0	38	36/50	1.9	2.0	15	165
AC751	200-700	13.0	12.5	12.0	0.4	0.6	1.9	2.4	2.9	4.8	4.0	3.5	20	20/27	1.7/1.9	1.9/2.0	5	11

Current data sheets available on website. Shaded models indicate typical output power ≥+20 dBm. ^ Not available in surface mount package.
 † See AC505/AC555 data sheet; see AC556/AC576 data sheet.

High Performance Cascadable Amplifiers

Typical and Guaranteed Specifications—50 Ω System

Model	Frequency Range MHz	Small Signal Gain dB			Gain Flatness ±dB		Noise Figure dB			Power Output At 1dB Compression dBm			Rev. Iso. dB	Intercept Point dBm	SWR In/Out		D.C.	
		Typ.	Min. 0/50C	Min. -55/85C	Max. 0/50C	Max. -55/85C	Typ.	Max. 0/50C	Max. -55/85C	Typ.	Min. 0/50C	Min. -55/85C			Typ.	3rd/2nd Typ.	Max. 0/50C	Max. -55/85C
Models listed by model number																		
AC829	10-800	12.0	11.5	11.0	0.3	0.4	3.0	4.0	4.7	18.5	17.0	16.5	18.5	33/41	1.8	1.9	5	50
AC838	10-800	30.0	29.0	28.0	0.7	0.9	3.0	3.5	4.0	16.0	15.0	14.5	37	30/50	1.7	1.9	5	73
AC847	10-800	13.3	12.5	12.0	0.5	0.7	3.0	3.5	4.0	17.0	16.0	15.5	17.5	32/47	1.7	1.9	15	44
AC848	10-800	13.2	12.5	12.0	0.4	0.5	4.0	4.5	5.0	19.3	18.5	18.0	17	34/43	1.8	2.0	15	58
AC885	800-900	20.0	18.5	17.5	0.7	0.9	1.0	1.3	1.6	13.0	12.0	11.5	36	27/42	2.0	2.0	5	90
AC936	10-900	27.5	27.0	26.5	0.6	0.8	3.3	3.8	4.5	10.0	9.0	8.5	38	22/40	1.6	1.8	5	35
AC986	800-900	30.3	29.8	29.3	0.3	0.4	1.3	1.8	2.3	22.5	21.0	20.5	44	33/50	1.7	1.8	15	135
AC1008	5-1000	15.5	14.8	14.3	0.4	0.5	4.5	5.5	6.0	18.5	18.0	17.5	20	33/44	1.7	1.8	15	85
AC1012	0.3-1000	16.0	15.0	14.5	0.7	0.8	3.2	3.7	4.2	9.0	7.0	7.0	20	21/33	1.7	2.0	15	24
AC1015	0.3-1000	15.0	14.0	13.5	0.7	0.8	3.4	4.0	4.5	9.0	7.0	7.0	20	21/33	1.7	2.0	15	24
AC1017	10-1000	12.0	11.5	11.0	0.5	0.7	4.2	5.0	5.5	15.2	14.5	14.0	17	30/45	1.5	1.8	15	44
AC1018	10-1000	14.5	14.0	13.5	0.5	0.8	3.8	5.0	5.5	15.8	15.0	14.5	18	30/44	1.8	2.0	15	44
AC1019	10-1000	11.5	10.5	10.0	0.5	0.8	4.5	6.0	6.5	22.0	20.0	19.5	16	35/44	1.8	2.0	15	90
AC1022	5-1000	16.2	15.5	15.0	0.5	0.7	2.3	2.8	3.5	-2.0	-2.5	-3.0	20	11/11	1.5	1.8	15	9
AC1035	10-1000	25.0	24.5	24.0	0.8	1.0	2.5	3.0	3.5	5.0	3.0	2.5	37	15/38	2.0	2.1	5	18
AC1036	10-1000	26.0	24.5	24.0	0.8	1.0	2.7	3.5	4.0	10.5	8.5	8.0	36	22/40	1.9	2.0	5	34
AC1038	5-1000	25.5	24.5	24.0	0.6	0.7	3.6	4.1	4.7	16.5	15.0	14.5	34	28/41	1.8	1.9	5	70
ARJ1049	20-1000	11.0	10.0	9.5	1.3	1.5	4.0	4.5	5.0	32.5	30.0	(29.5)	22	42/74	2.0	2.1	15	600
AP1051	10-1000	11.5	10.3	10.0	0.8	1.0	1.5	2.5	3.0	23.0	20.0	19.0	17	35/52	2.0	2.1	8	89
AP1053	10-1000	11.0	10.5	10.0	0.8	1.0	1.5	2.5	3.0	26.0	25.0	24.5	18	39/58	1.9	2.0	15	100
AC1054	5-1000	13.2	12.7	12.0	0.5	0.7	5.0	5.5	6.0	7.0	6.0	5.5	60	20/26	1.8	2.0	15	30
AC1057	0.3-1000	9.8	9.0	8.5	0.5	0.9	5.0	6.5	7.0	14.0	13.0	13.0	17	27.5/36	1.8	2.0	15	44
AP1060	10-1000	14.1	13.3	12.8	0.4	0.5	4.2	4.7	5.2	24.0	23.0	22.5	18	38/43	1.9	2.0	15	125
AC1063†	5-1000	16.2	15.5	15.0	0.5	0.7	2.5	3.0	4.0	5.5	3.0	2.5	20	15/20	1.5	1.8	15	14
AC1066	10-1000	27.5	26.5	25.5	0.5	0.8	3.3	4.0	4.5	15.5	14.5	14.0	36	28/45	1.8	2.0	15	65
AC1068	10-1000	24.5	23.5	22.5	0.5	0.7	3.7	5.0	5.5	18.5	17.5	17.0	34	32/48	1.7	1.8	15	97
AC1069	10-1000	24.5	23.5	22.5	0.5	0.7	4.0	5.5	6.0	21.5	20.0	19.5	34	34/45	1.7	1.8	15	129
AC1082	10-1000	14.8	14.0	13.5	0.5	0.7	3.5	4.5	5.0	12.8	12.0	11.5	18	26.5/37	1.8	1.8	5	30
AC1088	100-1000	18.5	17.5	17.0	0.6	0.7	1.1	1.2	1.5	21.0	20.5	20.0	24	35/50	1.9	2.0	5	80
AR1094	650-1100	14.0	13.5	12.7	0.3	0.4	2.1	2.6	3.1	26.5	25.5	25.0	20	40/55	1.8/1.9	1.9/2.0	15	175
AR1096	600-1000	14.2	13.5	13.0	0.4	0.5	2.1	2.7	3.2	28.0	27.0	26.5	21	42/58	1.7/1.9	1.9/2.1	15	230
AP1097	10-1000	13.2	12.5	11.5	1.0	1.1	3.5	4.5	5.0	26.5	25.5	25.0	22	39/55	1.8/1.9	1.9/2.0	15	175
AP1207	10-1200	11.0	10.0	9.5	0.5	0.8	2.8	3.5	4.0	25.5	24.5	24.0	20	43/66	1.8	2.0	15	188
AR1208	10-1200	13.0	12.5	12.0	0.7	0.9	4.3	4.8	5.3	18.0	17.5	17.0	18	31/64	1.7/2.0	1.8/2.1	15	93
AS1209	100-1200	28.0	27.0	26.5	0.6	0.8	1.0	1.5	1.7	19.8	19.0	18.5	40	33/49	1.8/1.5	2.0/1.7	5	171
AC1215	0.3-1200	15.0	14.5	14.0	0.5	0.7	3.7	4.2	4.7	12.5	12.0	11.5	20	26/37	1.7	1.9	15	35
AC1218	10-1200	11.5	10.5	10.0	0.5	0.7	4.5	5.5	6.5	19.0	17.5	17.0	16	33/45	1.8	2.0	15	65
AC1219	10-1200	11.5	10.5	10.0	0.5	0.7	4.5	5.5	6.5	22.0	20.5	20.0	16	32/37	1.8	2.0	15	88
AC1226	10-1200	22.5	21.0	20.0	0.6	0.9	3.6	4.5	5.0	16.5	16.0	15.5	33	30/45	1.6	1.8	15	72
AC1227	0.3-1200	12.3	11.0	10.5	0.5	0.8	4.3	5.0	5.5	14.0	13.0	12.5	18	28/40	1.8	1.8	15	44
AC1228	10-1200	11.0	10.5	10.0	0.5	0.7	4.5	5.5	6.0	17.5	16.5	16.0	16	29/36	1.8	2.0	15	55
AC1264	10-1200	26.0	25.0	24.5	0.6	0.8	2.9	3.5	4.0	8.0	7.0	7.0	35	21/44	1.7	1.9	15	35
AC1266	10-1200	23.5	22.0	21.5	0.6	0.9	3.5	4.0	4.5	14.9	14.0	13.5	34	28/46	1.7	1.9	15	65
AC1269	10-1200	21.0	20.0	19.0	0.5	0.8	4.2	5.5	6.0	21.0	20.0	19.5	32	34/50	1.8	2.0	15	130
AC1286	650-1200	31.0	28.0	27.0	0.6	0.7	1.0	1.3	1.7	12.0	10.5	9.5	42	23/35	1.8/1.9	2.0	15	62
AC1291	30-1400	18.0	16.5	16.0	0.9	1.0	<1.3	1.5	1.8	19.5	18.5	18.0	22	32/45	1.8	1.9	5	63
AC1292	30-1400	18.5	17.0	16.5	0.7	0.8	<1.3	1.5	1.8	22.0	21.0	20.5	23	36/50	1.8	1.9	5	100

Current data sheets available on website. Shaded models indicate typical output power ≥+20 dBm. † See AC1022/AC1063 data sheet.
 () Indicates minimum temperature at -55/+71°C.

